

Reco-Cool Coolguard OAT TF Pre-Diluted Antifreeze/ Coolant

Long Life Organic Acid Technology (OAT) Coolant TF Pre-Diluted

Reco-Cool Coolguard OAT TF Pre-Diluted Antifreeze/ Coolant is a fully formulated, long-life organic additive technology designed for use in both automotive and heavy-duty diesel engine coolant applications. It is 'ready to use', and is free of silicates, phosphates, borates, nitrites, and amines. This product requires no further dilution prior to use.

Applications

Reco-Cool Coolguard OAT TF Pre-Diluted Antifreeze/ Coolant is based on Recochem proprietary organic additive technology.

The primary corrosion inhibitors in this product have shown little depletion from original levels during extensive laboratory experiments, controlled fleet trials, and commercial use.

The product is a high performance long life automotive coolant for use in automotive applications, where other similarly formulated products are used. The product can also be used with confidence in light, medium and heavy duty road transport diesel powered vehicles.

The product is ready to use and requires no further dilution prior to use.

Performance Features and Benefits

- **Long life organic additive technology**

This product when used in automotive applications is suitable for up to 5 years or 250,000km, whichever comes first.

- **Free from silicates, phosphates, borates, nitrites and amines**

When used in long haul or heavy-duty applications, there is no need to charge initially the fresh coolant with SCAs.

- **Compatibility**

This product is fully compatible with other similarly formulated organic additive technology long life engine coolants. The product is also widely compatible with other silicate-free engine coolants.

- **Extended shelf life**

When stored undercover, away from moisture and direct sunlight, this product should be suitable for use for up to two years after manufacture.

Specifications and Approvals

Reco-Cool Coolguard OAT TF Pre-Diluted Antifreeze/ Coolant is recommended for use where the following industry and OEM specifications are required:-

ASTM	D3306 / D4985 /D6210-10 /D7583
AS/NZS	2108:2004 Type A
AFNOR	NFR 15-601
BS	6580
JIS	K2234
SAE	J1034/J1941
DDC	93K217
GM	1825M/1899M/6277M, Heavy Truck
GM	DEX-COOL™ <small>(not licenced but suitable for use)</small>
FORD	WSS-M97B44-D
Renault	Type D
VW	TL 774 F
Audi/Porsche	TL 774 F
Nissan	NES 5059 LLC
Peugeot	B71 5110

Health & Safety

Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained from your Recochem representative.

Protect the Environment

Take used coolant products to an authorised collection point. Do not discharge into drains, soil or water.



Typical Physical and Chemical Characteristics

Reco-Cool Coolguard OAT TF Pre-Diluted Antifreeze/ Coolant	Method	Units	Performance
Appearance	Visual		Blue/Green, Clear and Bright Fluid
pH (as is)	ASTM D 1287		7.5 – 9.0
Reserve Alkalinity	ASTM D 11121	mL 0.1N HCL	1.5 min
Specific Gravity (15 DegC)	ASTM D 1122	kg/L	1.010 – 1.020
Freeze Point (as is)	ASTM D 1177	Deg C	-4
Chloride	ASTM D 3634	Ppm	25 max
Foaming Properties	ASTM D 1881	mL Seconds	150 max 5.0 max

These characteristics are typical of current production. Whilst future production will conform to Recochem's specification, variations in these characteristics may occur.

